

1 CRDi Solutions

Common Rail Revolutionary testing solutions for BOSCH, DELPHI, DENSO and VDO Heavy Duty and Light Duty applications All types Piezo, Solenoid & Dual-Solenoid actuators.

CRU.4R









CRU.4R

Test Bench for 4 CRDi's Up to 2500Bar HP with 6.5 bar air supply Injector Coding for Delphi C2i/C3i, Bosch IMA/ISA, Denso QR and VDO IIC

Dynamic Electronic Mass Measurement (BK) Acc: 0.2%FS, repeatability: 0.05%

Under 25min testing phase

Fully Automatic Operation

Diesel Specialist level of Diagnosis

10" Touchscreen HMI

Capable of EUI/EUP and HEUI Testing with optional Attachment units

VDO/Bosch/Denso Piezo Stack Regeneration function

CGL: VDO Automatic

Valve Lift Gap Measurement

Blue Limits Diagnosis



View CZ CRU4R Tutorial Video



https://youtu.be/idOKGpnkAH0





BK Dynamic Electronic Mass Measurement



Analog Volumetric Measurement



Electronic Static Mass Measurement



Tests Performed

R2LC

Electrical actuator test for $k\Omega/\mu F$, $\Omega/\mu H$

CFL

Check For Leaks test (injector internal or external)

NI T

Nozzle Leakage Test

IKT

Static Back Leak Test

aNOP

Automatic Nozzle Opening Pressure test

iVM (FL, PL, EM, LL, PI)

Injector Volume Measuring test (full-load, part-load, emissions, low-load, pre/post-injection tests and more...)

iVM-DFI

Injector Volume Measuring test (multiple test-points slope per Pressure)

RSF

Injector nozzle Response-time test

SPR

Dynamic Spray test performed in all testing conditions

Features

iPSC

Illuminated Pressurized spray chamber

View of injection pattern up to 2500Bar

Visually diagnose NOP, incorrect spraying, leaky / seized injectors

RSP

Sensor adaptable to all nozzles

Precise measurement of nozzle reaction time

Easily diagnose a slow acting injector, a retarded injection event, poor engine performance and emissions issues.

AZO Software

Advanced Android based HMI/PC

Wi-Fi printing, sharing, syncing, software/hardware & database updating, via USB or WiFi Real-time Oscilloscope and CSV data export

TeamViewer Support and more...

Reports

Easy fail-track color report for each injector.

Single-page Quick report or Multi-page Analytic reporting





& types

Specifications

& User Database

actuation profiles (HV: 0-300 Volts / 0-35A)

(StG. StB. SC. OC. IC)

& robust design

before testing*

All Makes OE Manufacturer

Developer and OE customizing

Piezo & Solenoid programmable

Injector & PCB protection circuit

User friendly, ergonomic, dynamic

Spill-free hose quick connectors

aMACC – Automatic chemical treatment and flushing of the injector

Complementary set of CRi adapters,

fittings and connectors for all makes

Multiple Injections capability

* Available Optionals ** Future Updates